

# HIGH MAST LIGHT STADIUM LIGHT SERIES

LED



### TECHNICAL DATA

<b>Input voltage</b>	100 - 277 V~ (Multivoltage)
<b>Input frequency</b>	50 / 60 Hz
<b>Dimmable</b>	0 - 10 V
<b>Color temperature</b>	5,000K
<b>IRC</b>	>80
<b>Operating temperature</b>	-40 to 50 °C
<b>Harmonic distortion</b>	<10%
<b>Power factor</b>	0.99
<b>Opening angle</b>	15°, 20°, 40° or 60°.
<b>Mounting</b>	Rotable Bracket
<b>Ranking</b>	IP66 - IK10
<b>Surge protection</b>	10 kV
<b>Light maintenance @100,000 hours</b>	0.86 <small>*Projected L70 (12K) ≥ 72,000 hours according to IES TM-21</small>
<b>Body</b>	Die-cast aluminum alloy
<b>Optics</b>	Polycarbonate
<b>Color</b>	Gray

# JUNGO LIGHTING

Jungo Lighting's **Stadium Light Series** illuminates the playing field with state-of-the-art technology. Designed for high competition and major sporting feats, the Stadium Series offers precision lighting with unmatched energy efficiency and performance. Each luminaire is built to maximize visibility, reduce glare and provide the durability to withstand all weather conditions.

### CERTIFICATES



Model	Adjustable Power	Luminous Efficiency	Luminous flux
SO	600 W   700 W   800 W	160 lm   W	MAX. 128,000 lm


### KEY FEATURES

Interchangeable visor with different sizes available.

Handles for easy handling.



Adjustable Power



Power adjustable by switch.

Blade switch for easy maintenance.



High transmissivity polycarbonate optics.



**Jungo Connect** is a complete and highly scalable central management system for lighting and IoT devices with multi-protocol support (Zigbee, BluetoothMesh, Wi-Fi, NB- IoT, 4G LTE) compatibility that meets all the devices and energy management needs of a smart industrial or commercial building.

