



HAZARDOUS LOCATIONS

**EXS02-A** SERIES

Ensure safe evacuation during power outages with this emergency luminaire. It provides **up to 180 minutes** of illumination, featuring a double-sided, continuously lit EXIT sign and two adjustable LED heads for targeted lighting. Designed for hazardous areas, it delivers reliable performance when it matters most, guiding occupants to safety with confidence.

CERTIFICATIONS



Technical Data	
Input voltage	100 - 277V ~ (Multi-voltage)
Input frequency	50 / 60 Hz
Dimmable	NA
Color temperature	5000K
CRI	> 75
Operating temperature	-20 to 60° C
Harmonic distortion	<10 %
Power factor	0.95
Beam angle	120°
Mounting	Surface mount: Wall base (included)
Classification	IP66
Impact resistance	IK08
Anti-surge rating	2 kV
Light maintenance @100,000 hrs	0.86 *Projected L70 (I2K) ≥72,000 hrs per IESTM-21
Body	Die-cast A383 aluminum alloy
Optics	Polycarbonate
Color	Yellow

Model	Nominal Power	Luminous Efficiency	Luminous Flux
EXS02-A	6 W	130 lm/W	780 lumens



**ATEX - European Union**  
II2 G Ex db op is IIB+H T6 Gb 2  
II2 D Ex tb IIIC T70°C Db IP66

**Other Classifications**  
IP66  
IK10




**IECEX - International**  
Ex db IIB+H T6 Gb  
Ex tb IIIC T70°C Db


Dimensions

**EXS02-A**

9.5 kg



Photometric distribution



Control Systems



To download the IES file, visit:  
[Jungo.Lighting/recursos](http://Jungo.Lighting/recursos)