



HAZARDOUS LOCATIONS

EXS03-A SERIES

Easily locate emergency exits during power outages. Provides illumination for **up to 180 minutes**, allowing you to evacuate safely and calmly. It features double-sided EXIT signage that remains illuminated at all times and two LED heads to direct light where it's needed. With this emergency luminaire, you can be confident that you'll have the proper lighting to evacuate quickly and smoothly in case of an emergency in hazardous areas.

CERTIFICATIONS



Technical Data	
Input voltage	100 - 277V ~ (Multi-voltage)
Input frequency	50 / 60 Hz
Dimmable	NA
Color temperature	5000K
CRI	> 75
Operating temperature	-20 to 60° C
Harmonic distortion	<10 %
Power factor	0.95
Beam angle	120°
Mounting	Surface mount: Wall base (included)
Classification	IP66
Impact resistance	IK08
Anti-surge rating	2 kV
Light maintenance @100,000 hrs	0.86 *Projected L70 (I2K) ≥72,000 hrs per IESTM-21
Body	Die-cast A360 aluminum alloy
Optics	Polycarbonate
Color	Yellow

Model	Nominal Power	Luminous Efficiency	Luminous Flux
EXS03-A	6 W	130 lm/W	1300 lumens



Intertek - North America
Class I, Division 1, Groups C, D
Class I, Division 2, Groups A, B, C, D
Class II, Division 1, Groups E, F, G
Class II, Division 2, Groups F, G
Class III Class III




Intertek - North America
UL844, UL924
Other Classifications
IP66


Dimensions

EXS03-A

25 kg



Photometric distribution



Control Systems



To download the IES file, visit:
Jungo.Lighting/recursos